



For Drop-in Anchors




SDS-PLUS + STOP Rotary Hammer Bit

- ◆ Rotary Hammer Drill
- ◆ STOP - Lip Prevents Over-Drilling
- ◆ Drill Exact Depth For Drop-In Anchor
- ◆ Less Likely to Hit Rebar
- ◆ ANSI Specification




Part #	Size	Drill Depth	Anchor Size	Qty.	List
STP-617	3/8"	1-1/16"	1/4"	1	\$24.75
STP-813	1/2"	13/16"	3/8" Short	1	\$27.50
STP-827	1/2"	1-11/16"	3/8"	1	\$28.88
STP-1019	5/8"	1-3/16"	1/2" Short	1	\$30.92
STP-1033	5/8"	2-1/16"	1/2"	1	\$35.13
STP-418	7/8"	2-5/8"	5/8"	1	\$38.64
STP-419	1"	3-1/4"	3/4"	1	\$45.59

Use Your SDS-Plus Drill Bits In Larger SDS-MAX® Or Spline Drive Machines:



Adapter



Adapter

SDS-MAX® to SDS-PLUS

Part #	Description	List
725MAX001	SDS-MAX To SDS-Plus Adapter	\$114.15



Spline to SDS-PLUS

Part #	Description	List
725SP001	Spline To SDS-Plus Adapter	\$118.12



Replacement Kit - FOR ADAPTERS

Part #	Description	List
715KIT001	Gaskets & Ball Bearings	\$4.50

SDS-Max to SDS-Plus Adapter



X-Tend Your Drilling Depths!



Drill bit extension system for all SDS-Max & Spline machines.

- ◆ X-Tend Any SDS-MAX Tool
- ◆ Quick & Safe Connection
- ◆ Simple To Use
- ◆ No Energy Loss
- ◆ No Weak Points
- ◆ Saves Time & Money
- ◆ Reduces Tool Requirements

How it works:

- X-Tendr™ Adapter has double locking SDS-MAX inputs.
- All EXTENSION SHAFTS have 1 SDS-MAX end which locks into X-Tendr™ Adapter. Other end can be inserted into either an SDS-MAX or Spline machine.
- X-Tend any SDS-MAX drill bit, core bit, tunnel bore drill, drill head, or chisel.
- Reach of X-Tendr™ system limited to 1 adapter and 1 extension.



X-Tendr™ - MAX to MAX SHANK ADAPTER

Part #	Description	List
XT6700	Adapter (1-3/16" x 7-1/2")	\$384.25
XT6750	Adapter Grease (Tube)	\$7.17

Drill Bit Diameter Must Be 1-1/4" Or Larger if X-Tendr™ is to Pass Through Hole Being Drilled.



X-Tendr™ Extension Shafts

Part #	OAL	Shank	List
XT6701	12-1/2"	SDS-MAX	\$60.67
XT6702	30"	SDS-MAX	\$74.58
XT6703	44"	SDS-MAX	\$101.79
XT6708	12-1/2"	SPLINE	\$74.28
XT6709	30"	SPLINE	\$92.98



1. Choose either SDS-MAX or SPLINE Drive and desired length Extension.



2. Attach X-Tendr™ Adaptor to SDS-MAX end of Extension.



3. Attach desired SDS-MAX Rotary Hammer Drill Bit, Core Bit, Tunnel Bore Drill or Chisel.

Drill Bit Diameter Must Be 1-1/4" Or Larger if X-Tendr™ is to Pass Through Hole Being Drilled.

X-TEND YOUR OPTIONS...

